

Ref. No. NML-DGP/ENV/25/083

Date: 25th September 2025

To
The Member Secretary,
West Bengal Pollution Control Board,
Paribesh Bhawan,
10A, Block - LA, Sector - III,
Salt Lake City,
Kolkata - 700109, (West Bengal)

Sub: Environmental statement (Form-V) of Neo Metaliks Ltd., Durgapur for the financial year 2024-25.

Dear Sir,

We are herewith submitting the Annual Environmental Statement duly filled in Form-V for the financial year ending 31st March 2025 for your kind information and record.

Thanking You

Yours faithfully,

For Neo Metaliks Ltd.,



(Authorized Signatory)



Encl: As above.

CC: The Environmental Engineer (In-Charge), West Bengal Pollution Control Board, Durgapur Regional Office (Paribesh Bhaban), Sahid Khudiram Sarani, City Centre, Durgapur- 713216.

[FORM-V]

(See rule 14)

Environmental Statement for the financial year ending the 31st March 2025

PART-A

1	Name and address of the owner/occupier of the industry, operation or process	Mr. Dhiraj Kumar Pandey, Factory Manager, Neo Metaliks Limited, Gopalpur, Durgapur, West Bengal-713212.
2	Industry Category Primary – (STC Code) Secondary –(SIC Code)	Primary- (STC Code): GSTIN No-19AABCN8514G1ZE Secondary – (SIC Code): 3312
3	Production Capacity	Pig Iron: 15666 MT/Month, Sintered Iron: 47,475 MT/Month, Captive Power: 10 MW
4	Year of Establishment	2006
5	Date of the last environmental Statement submitted	26 th September, 2024

Part-B

Water and Raw material Consumption

1. Water consumption M³/day

Process	Nil
Cooling	405
Boiler Feed	18
Domestic	16

Name of the Products	Process water consumption per unit of product output (M ³ /T)	
	During the previous financial year (2023-24)	During the current financial year (2024-25)
Pig Iron	Water is not used in the process	Water is not used in the process

2. Raw material Consumption

Name of the raw material	Name of the Products	Consumption of raw material per unit of output (in MT)	
		During the previous financial year(2023-24)	During the current financial year (2024-25)
Iron Ore Fines	Pig Iron	0.651	0.640
Iron Ore & Screened		0.619	0.606
Iron Ore Pellet		0	0
Coke Fines		0.074	0.053
Coke & Screened		0.566	0.591
Lime-Stone		0.121	0.085



Lime-Stone Fines		0.021	0.038
Quick Lime		0	0.001
Dolomite Fines		0.033	0.029
Dolomite		0.061	0.076
Quartzite		0.019	0.010
Gravel		0	0
Energy/Power (KWh/T)		120	118

PART-C

Pollution discharged to environment/unit of output

(Parameter as specified in the consent issued)

Pollutants	Quantity of Pollutants discharged (mass/day)	Concentration of Pollutants in discharges (Mass/volume)			Percentage of variation from prescribed standards with reasons
		Parameters	Average Results (annually)	Max. Permissible Limit of SPC Board	
(A) Water: Zero Liquid Discharge- Cooling water is completely recycled. Plant waste water is treated and recycled for slag cooling, dust suppression. Sanitary effluent is treated in septic tanks and soaks pits. Canteen waste is treated in oil water separator and then used for plantation/gardening. Hence, there is no generation of effluent from the industry.					
Domestic Effluent	NIL	pH TSS (mg/l) BOD (mg/l) COD(mg/l) Oil & Grease (mg/l)	7.4 26.0 21.8 84 3.9	5.5 – 9.0 100 30 250 10	All the parameters are well within the standard.
Pollutants	Quantity of pollutants discharged (mass/day)	Concentrations of pollutants discharges (Mass/volume)	Standard (mg/Nm ³)	Percentage of variation from prescribed standards with reasons	
(B) Air Particulate Matter (PM)					
Flue gas from Sinter Plant -1 Head ESP Stack	67.9	38.8	100 mg/Nm ³	Well within the WBPCB prescribed standard	
Flue gas from Sinter Plant-1	35.5	24.3	100 mg/Nm ³		




Handwritten initials/signature.

Tail ESP Stack				
Flue gas from MBF Stack	53.8	27	150 mg/Nm ³	
Flue gas from CPP (4.5MW) Stack	39	56.3	100 mg/Nm ³	
Flue gas from CPP (10MW) Stack	6.5	22	30 mg/Nm ³	
Flue gas from Sinter Plant-2 Head ESP Stack	23.8	28	30 mg/Nm ³	

**PART-D
HAZARDOUS WASTES**

(As specified under Hazardous & Other Wastes [Management and Transboundary Movement] Rules, 2016 and amendment thereof)

Hazardous wastes	Total quantity	
	During the previous financial year 2023-24	During the current financial year 2024-25
A. From Process:		
1. Used oil		1. Opening Balance-0 ton,
2. Spent ion exchange Resin	1. Opening Balance-0.280 ton, Generated-0.655 ton & Disposed- 0.935 ton	Generated- 1.54 ton & Disposed- 1.54 ton
3. Spent Carbon or filter medium (D.G. set oil filter)	Balance Quantity- NIL	Balance Quantity- NIL
	2. Generated & Disposed - 0.690 ton.	2. Generated & Disposed - 0.600 ton.
	Balance Quantity- NIL	Balance Quantity- NIL
	3. Generated & Disposed - 0.020 ton.	3. Generated & Disposed - 0.020 ton.
	Balance Quantity- NIL	Balance Quantity- NIL
B. From pollution control facilities	NIL	NIL



PART-E
Solid Wastes

	Total quantity (MT)	
	During the previous financial year (2023-24)	During the current financial year (2024-25)
Generation from Process	Granulated Slag-103550	Granulated Slag-92230
From pollution control facilities	Flue Dust- 3470	Flue Dust- 1518
1. Quantity recycled or re-utilized with the unit	1. Flue Dust- 2474.77	1. Flue Dust- 1609
Sold	2. Granulated Slag- 102725.91.	2. Granulated Slag- 91636
Disposed	3. NA	Flue Dust- 2497
		3. NA

PART-F

(Please specify the characterizations (in terms of composition of quantum) of hazardous as well as solid wastes and indicate disposal practice adopted for both these categories of wastes)

The table outlines the details pertaining to the characterization and disposal practices adopted at our site for hazardous wastes as well as solid wastes.

Name of Wastes	Characterization	Disposal Practices
a. Hazardous waste Used Oil	Combustible liquid, Carcinogenic, Eco-toxic.	Sold to authorized recyclers registered with WBPCB.
Spent ion exchange Resin	Flammable solid, Eco-toxic.	Disposed to CHWTSDF.
Spent Carbon or filter medium (D.G. set oil filter)	Combustible solid, Eco-toxic.	Disposed to CHWTSDF.
b. Solid Wastes	Characteristics	Method of disposal
Granulated Slag	SiO ₂ - 32.39 % CaO- 34.45 % MgO- 7.39 % Al ₂ O ₃ -19.99 % FeO- 0.71 % S - 0.65 % Na ₂ O- 0.27 %	Sold to cement industry for making of Portland Slag Cement.



Flue Dust	Fe ₂ O ₃ - 52.62 % SiO ₂ - 8.96 % CaO- 5.36 % MgO- 2.36 % Al ₂ O ₃ -4.82 % Na ₂ O- 0.18% VM-2.47% ASH-74.33% FC-23.20%	Reutilized in-house sinter making process.
-----------	--	--

Part-G

(Impact of pollution abatement measures taken for conservation of Natural resources and on the cost of production)

- Waste Heat from Sinter Cooler is being utilized in Coke Drying Purpose.
- Economizer & Air Pre Heater (APH) are being used to recover Waste Heat from Flue Gas at Waste Heat Recovery Boiler.
- Recuperator is being used for Heat recovery from Flue Gas and that heat is being utilized for Stove heating purpose.
- Steam trap plug is installed to restrict the leakages in WHRB.
- Energy Committee is formed at MBF by involving different senior & junior people from departments to identify & lead Energy Saving Projects.
- The technology of Pulverized Coal Injection (PCI) to Mini Blast Furnace (MBF) has been practiced.
- Rainwater Harvesting Pits have been installed at different locations inside plant premises to recharge ground water.
- To utilize treated water and control fugitive emission during movement of vehicles, water sprinkling through water tanker has been provided on the internal roads. If required, cover nearby roads outside plant premises also.
- Cross-functional Water Management team has been formed to look after the water management inside plant premises. Focusing on reduction in water consumption, minimizing water losses, to explore water conservation projects, identifying water leakages & immediately taking action to arrest the same.
- Green Belt Development is our on-going activity. Extensive tree plantation is being carried out every year in all open spaces available in and around the plant premises.
- Various environmental management programs have been taken up to conserve natural resources like raw materials and water. To reduce specific power consumption, FO consumption and to minimize waste generation various environmental management programs are being taken up and their progress is reviewed from time to time. Targets are being fixed to various user departments to control raw material consumption, water consumption, power consumption, FO consumption etc.
- Organic Waste Composter (OWC) machine is installed & being operated near canteen for composting kitchen Waste. The bio-compost produced is being utilized in gardening, vegetation and plantation activities.
- Neo Metaliks Ltd. (Durgapur) is certified ISO 9001:2015, ISO 14001:2015 & ISO 45001:2018 standards.



Part-H

(Additional measures/investment proposal for environmental protection including abatement of Pollution)

- In-plant control measures, De-Dusting System with Bag Filters, Fume Extraction system have been installed at vulnerable sources of fugitive emission.
- Stack emissions have been maintained within norms by operating Head ESP & Tail ESP of Sinter Plant, GCP of MBF etc.
- Sufficient spares like I.D. fan, impeller, shaft, bearings, bearing housings, V belts, gear box spares, filter bags, cages etc., required for continuous operation of gas cleaning plant, Bag house, ESPs are maintained in stock for immediate replacement, in case of any failure.
- To monitor stack emission, 24x7 continuous emission monitoring system (CEMS) have been installed at process stacks like Sinter Plant Head & Tail ESP, Blast Furnace GCP & Captive Power Plant and real time online data is being transmitted to WBPCB & CPCB Server
- Portable Water sprinklers are provided at various locations like RMHS area, Sinter Screen & Crusher House area, MBF Ground Hopper area & Pig Yard etc. for suppression of fugitive dust emission.
- Roof top rain water harvesting sumps are made and accumulated rain water being used for cooling & dust suppression purpose.
- Mobile water tankers have been engaged & being operated to minimize dust generation because of vehicular movement.
- 02 nos. of high pressurized Rain Guns at Weigh Bridge & Pig Yard and 05 no. of Water Fog Cannon at RMHS and Sinter plant area have been installed & being operated respectively for abatement of air pollution.
- Plant internal roads vehicle movement areas and workplaces are developed with concreted/pavered.
- As on 31.03.2025, a total of 30323 nos. of saplings have been planted with native species covering 30.2 % area. Another 3800 nos. of saplings have been planted in the local village in the vicinity of the plant in FY 2024-25.
- All the raw Materials like Iron ore lump & fines, flux and coke & coke fines are kept covered with Tarpaulin.
- All the conveyors and transfer points have been enclosed to reduce secondary fugitive emission.
- Roof Top Solar Photovoltaic (SPV) Power System of 10 KWp capacity has been installed at roof-top of New Admin Building. In addition to this, old halogen/mercury lights are being replaced with LED lights progressively at various locations in phase-wise manner. In new plant we have installed all LED lights.
- 03 numbers of Continuous Ambient Air Quality Monitoring Stations (CAAQMS) are proposed to be installed at 03 different locations inside plant premises for ambient air quality monitoring and connected to WBPCB & CPCB server through RTDAS.




Part-I

(Any other particulars for improving the quality of the environment)

Besides the existing facilities, the following measures/investments have been proposed during FY 2025-26 for environmental protection and abatement of pollution.

- ❖ Provision for one Wheel washing mechanism with complete recirculation system has been proposed near the main gate.
- ❖ Construction of concrete & paved roads shall be done in a phase wise manner.
- ❖ Truck mounted Vacuum Cleaning Cum Road Sweeping Machine is proposed to be installed.
- ❖ Installation and commissioning of Dry Gas Cleaning Plant at MBF plant.
- ❖ Installation of Dry Fog Dust Suppression System at vulnerable sources of fugitive emission.
- ❖ Installation-commissioning of ETP & STP is also proposed to ensure Zero Discharge.
- ❖ Garland drains and collection pits are provided to arrest the run-off water in the event of heavy rains.
- ❖ As a part of disclosure of environmental parameters to all the stakeholders and to keep transparency, Environmental parameters w.r.t. ambient air as well as stack emissions & Drinking Water, Treated Water have been monitored bi-monthly through NABL accredited laboratory.
- ❖ Various Energy saving initiatives are being taken up regularly.
- ❖ Like every year, World Environment Day will be celebrated on 5th June'2024 with great enthusiasm and pertinent participation from NML employees, associate partner employees, family members etc. and Plantation activity will be carried out inside and outside of the plant premises.





Handwritten signature or initials.